


Features:








- Cooler running, outboard bearing provides maintenance-free operation
- Environmentally friendly oil-free technology
- Extremely quiet operation



- All motors are standard TEFC with Class F insulation, UL recognized, CE Compliant
Explosion-Proof motors available
- Custom construction blowers are available
- Rugged die cast aluminum construction

Performance curve for Vacuum pump



Performance curve for Compressor



Dimensions: (inches)

**Recommended
Accessories:**
Relief valve:

VC51Z (Vacuum)

PC51Z (Pressure)

Filter:

 ATF-125-1337
(Vacuum)

 AFS-20-125-10
(Pressure)

Specifications subject to change without notice. Please contact factory for specification updates.

Selection & Ordering Data - Type 3BA1330

| Curve No. | Order No. | Frequency | Rated power | Input voltage | Input current | Permissible total differential pressure ²⁾ | Sound pressure level ³⁾ | Weight ca. |
|-----------|-----------|-----------|-------------|---------------|---------------|---|------------------------------------|------------|
| | | Hz | HP | V | A | Vacuum inch H2O | Compressor inch H2O | lbs |

3~ 50/60 Hz IP55 insulation material class F

| | | | | | | | | | | | |
|-------|---------------|----|------|---------------|---------------|-------|-------|-----|----|----|----|
| A 150 | 3BA1330-7AT06 | 50 | 0.34 | 200D ... 240D | 345Y ... 415Y | 2.1 D | 1.2 Y | -32 | 28 | 54 | 23 |
| A 151 | 3BA1330-7AT06 | 60 | 0.39 | 220D ... 250D | 415Y ... 460Y | 1.74D | 1.0 Y | -36 | 32 | 57 | 19 |
| A 152 | 3BA1330-7AT16 | 50 | 0.54 | 200D ... 240D | 345Y ... 415Y | 2.6 D | 1.5 Y | -48 | 52 | 54 | 23 |
| A 153 | 3BA1330-7AT16 | 60 | 0.67 | 220D ... 250D | 415Y ... 460Y | 2.6 D | 1.5 Y | -60 | 64 | 57 | 23 |
| A 154 | 3BA1330-7AT26 | 50 | 0.94 | 200D ... 240D | 345Y ... 415Y | 3.8 D | 2.2 Y | -48 | 56 | 54 | 25 |
| A 155 | 3BA1330-7AT26 | 60 | 1.11 | 220D ... 250D | 415Y ... 460Y | 3.75D | 2.15Y | -64 | 72 | 57 | 25 |

3~ 50/60 Hz IP55 insulation material class F

| | | | | | | | | | | | |
|-------|---------------|----|------|------|--|-------|--|-----|----|----|----|
| A 150 | 3BA1330-7AT05 | 50 | 0.34 | 500D | | 0.72D | | -32 | 28 | 54 | 23 |
| A 151 | 3BA1330-7AT05 | 60 | 0.39 | 575D | | 0.76D | | -36 | 32 | 57 | 19 |
| A 152 | 3BA1330-7AT15 | 50 | 0.54 | 500D | | 1.0 D | | -48 | 52 | 54 | 23 |
| A 153 | 3BA1330-7AT15 | 60 | 0.67 | 575D | | 1.1 D | | -60 | 64 | 57 | 23 |
| A 154 | 3BA1330-7AT25 | 50 | 0.94 | 500D | | 1.88D | | -48 | 56 | 54 | 25 |
| A 155 | 3BA1330-7AT25 | 60 | 1.11 | 575D | | 1.76D | | -64 | 72 | 57 | 25 |

1~ 50/60 Hz IP55 with attached capacitor for continuous operation

| | | | | | | | | | | | |
|--------|---------------|----|------|-----|-----|-----|-----|-----|----|----|----|
| A 152s | 3BA1330-7AS15 | 50 | 0.50 | 115 | 230 | 5.4 | 2.7 | -44 | 44 | 54 | 23 |
| A 153s | 3BA1330-7AS15 | 60 | 0.60 | 115 | 230 | 6.0 | 3.0 | -52 | 56 | 57 | 23 |

Suitable for 208 Volt Operation

All curves are rated at 14.7 psia and 68°F ambient conditions and are reported in SCFM referenced to 68°F and 14.696 psia sea level conditions. Curve values are nominal, actual performance may vary by up to 10% of the values indicated. For inlet temperatures above approximately 80°F or for handling gases other than air, please contact your Airtech sales representative for assistance.